

65,084-0002

CARRIER TRANSFER MOLDING DEVICE

FIELD OF INVENTION

This invention relates to a polymer transfer and deposition system and to a carrier transfer molding system where a carrier of a generally planar shape passes below a polymer deposition device where polymer is deposited on the carrier with the combined carrier and polymer moving to a forming device to produce an article of a desired shape. When more than one layer of polymer is deposited on the carrier, an insert is placed between the polymer layers. A surface layer is laminated to the top layer of polymer prior to moving into a forming device.

CROSS REFERENCE TO RELATED APPLICATIONS

This invention refers to a transport and deposition device and method to incorporate continuous fibers in a polymer as described in U.S. Ser. No. 09/388,052 filed on September 1, 1999.

BACKGROUND OF INVENTION

This invention relates to a system including a combined carrier and deposited polymer that move into a forming device to produce an article of a desired shape. The carrier may collect more than one deposit or layer of polymer where an insert such as a rigid foam or honeycomb core is encapsulated by the polymer layers. Additionally, continuous strands of fiber reinforcement may be incorporated in the polymer phase. The carrier, as an example, is a film, foil, fiber construction or other support of a generally planar shape. The carrier provides a decorative surface in the finished shape, outdoor ultra-violet (UV) protection, fire retardency, improved chemical and permeation resistance, improved impact properties or just provides a sacrificial mechanism to move a deposited polymer into a forming device. Although a thermoset can be specified as the deposited

65,084-0002

polymer, a molten thermoplastic is the preferred choice. A method to deposit polymer onto a carrier in close proximity to one or more forming devices, to minimize heat loss time prior to forming the desired part, is described in my copending U.S. Patent application, Ser. No. 09/388,052. The same disclosure describes a method to incorporate continuous fibers in the polymer composition.

Although the carrier process or method can produce a wide variety of sizes and shapes, the processing advantages become more apparent as the size of the finished part increases, typically in excess of one square meter. A prime thermosetting method used to produce large polymer composites utilizes cross-linking liquid resins to impregnate reinforcements under low pressures, either within a mixing head or pumping the liquid into a fiber preform. The combined composite solidifies as the liquid polymer cross-links. Large thermoplastic composites can be produced under low pressure by a softening a plastic sheet, then pulling a vacuum under a forming shape. These low pressure processes are generally used where production volumes are lower because of the lower productivity associated with these technologies. Injection molding was designed for high volume production of polymer shapes. However, the process requires higher molding pressures. For large parts, these pressure requirements can be substantial. The increasing equipment costs associated with the need to meet increased pressures has limited the use of injection molding in the production of large parts.

The polymer deposited on a carrier generally occupies or fills out a large area of the forming dies in a forming press, plus the pre-coating of the carrier by a deposited polymer, leads to a reduction in trapped gases between the carrier and the polymer. Because the polymer flows less within a forming device when compared to injection molding, the pressure requirements needed to produce an article with a finished shape are less than required with an injection molding machine. This reduced pressure allows pressure sensitive surface materials and cores to be incorporated in the finished composite shape without damage. The processing cycle of the carrier deposited polymer process is similar to an injection molding cycle based on the similar cooling times and distribution of

65,084-0002

polymer within the forming device. The carrier transfer lower pressure process combines the productivity and processing characteristics of injection molding with the ability to customize the desired finished surface; incorporate cores to improve stiffness, acoustic and insulation properties, and allow selective placement of continuous reinforcement to increase the stiffness and strength of the composite.

SUMMARY OF THE INVENTION

The present invention addresses a need in the art by providing a combined polymer matrix where the surface characteristics of the product can be customized, cores can be incorporated and, where needed, reinforcement impregnation to produce a whole new range of useful properties. A carrier, typically in a planar shape, passes below a polymer deposition device where a uniform layer of molten polymer is deposited on the carrier in close proximity to a forming device. The combined materials move into an opening in the forming device where the forming device closes on the materials to form the desired shape.

The carrier moves under a polymer deposition device that contains a predetermined amount of molten polymer based on the size of the deposition chamber. A ram within the chamber pushes the molten polymer out of an opening in the bottom of the chamber where the size and shape of the opening determines the deposited thickness, together with the speed of the ram and carrier. The molten polymer may be polypropylene, high density polyethylene, polyester, thermoplastic olefin or any other desired thermoplastic. The carrier can be low cost non-wovens such as spunbonded polyester and polyolefin or felt; a combination of a film and non-woven or foam; a fluoropolymer film such as Fluorinated Ethylene Propylene (FEP) to improve fuel and gas permeation resistance or polyvinyl fluoride for fire retardency and UV resistance; a pre-printed film or a coated film to change the surface characteristics in the finished part or any other desired surface. The combined materials index in a straight line fashion into the forming press where the carrier is separated from a series of side clamps that support the carrier during the deposition and movement phase. Alternately, an undercarriage that holds the carrier in position during

65,084-0002

polymer deposition and movement into the forming device can support the carrier. A vacuum or clamps incorporated in the undercarriage would hold the carrier and deposited layer or layers of polymer during movement into the forming device, then disengage prior to removal of the undercarriage from the carrier and closing of the forming device. Outboard clamps located on opposite sides of the forming press and outside of the shaping molds would hold and position the combined carrier and deposited polymer as the forming device closed to produce the desired shape. Preferably, the undercarriage would be an insulator and have low surface friction characteristics.

In a second aspect, the carrier moves under the polymer deposition device in a direction away from the forming device as polymer is deposited on the carrier. Once clear of the deposition device, a multi-axis robot positions an insert on top of the deposited polymer layer. The carrier reverses direction, again passing under the polymer deposition device where a second coating or layer of polymer is deposited over the insert. The combined composite moves in a straight-line direction into the forming device to form a desired shape. The insert can be rigid foam, honeycomb, balsa or any other desired construction.

Alternately, two polymer deposition devices can align with each other in a manner where the carrier can pass under both devices in a straight-line direction with the forming device. The carrier first passes under the deposition device furthest from the forming device, then under the second deposition device where a second layer of polymer is deposited. The combined polymers and carrier move into the forming device where the desired shape is formed. Prior to the second deposit a multi-axis robot places an insert such as rigid foam or honeycomb on top of the first deposited layer prior to applying the second coating. The composition of the polymer being deposited from each deposition chamber can be the same or of a different polymer.

Using a secondary chamber that collects molten polymer from the deposition chamber, continuous fibers, discontinuous fibers or a combination of continuous and

65,084-0002

discontinuous fibers are fed into a chamber where the fibers are encapsulated by molten polymer under pressure and downward applied motion as described in my copending U.S. Patent application, Ser. No. 09/388,052. The combined material is deposited in generally a planar shape on the carrier and moves into the forming device to produce the desired shape.

A second surface layer can be applied to the deposited polymer prior to entering the forming device. A multi-axis robot contains a vertical holding fixture with a curved edge on the side closest to the deposited polymer. The surface layer is positioned on the fixture with the edge extending into the curved area. The robot applies downwardly acting pressure on the curved edge where the forward movement of the deposited polymer on the carrier pulls the surface layer from the robot fixture. The curved edge can incorporate a roller feature that assists the movement of the second surface layer. Alternately, drive rollers or other suitable driving devices can assist the forward movement of the second surface layer during lamination to the top of the deposited polymer melt.

A mold consisting of a cavity or concave side and a core or convex side can be attached to a vertical action-forming device such as a clamping press. The desired polymer and carrier composition would be positioned between the cavity and core where the press would close to form the product determined by the shape of the cavity and core. The carrier side can be formed over either the cavity or core. One reason for forming the carrier over the core side would be to produce a chamber with the carrier on the inside area. Two chambers with matching edges would be aligned opposite each other and fused together after softening the surfaces of the carrier edges with a source of heat generation directed at the area to be fused. A set of holding fixtures would move the two mating half's together under pressure to insure full contact at the bond line. The resulting part would be a hollow device such as a liquid container. Interior and exterior required details would be incorporated in either section of the parts. The use of a fluoropolymer construction as the carrier would provide improved chemical and permeation resistance through the inside

65,084-0002

walls of the container. A specific example would be a plastic fuel tank with molded-in attachment features and low fuel vapor permeation.

Any of the various carrier and polymer combinations can be incorporated together to form a specific finished article or part. For example, the carrier can provide a decorative surface with the deposited polymer adding structure. The incorporation of a core such as rigid foam between polymer layers can increase the stiffness, insulation properties or other desirable characteristic in the combined composite. Continuous fiber reinforcement in one or both polymer deposits would increase the stiffness and strength of the composite.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic top view of the components that made up the transfer deposition device.

Fig. 2 is a cross-sectional view of the polymer distribution manifold taken along line 2-2 of Fig. 1.

Fig. 3 is a cross-sectional view of the transport device taken along line 3-3 of Fig. 1.

Fig. 4 is a schematic view of the preferred carrier moving below a plasticized polymer chamber where polymer is being deposited and a forming device is in line with the carrier and deposition chamber.

Fig. 5 is a schematic view of a multi-axis robot placing a rectangular insert on a polymer deposited carrier and a supporting undercarriage containing side clamps to hold the carrier and a deposition chamber that applies another polymer deposit when the undercarriage moves under the chamber to encapsulate the insert.

65,084-0002

Fig. 6 is a schematic view of a robot positioned in front of a deposition chamber where a surface layer is released from the robot as a polymer deposited carrier and supporting undercarriage moves under the curved bottom section of robot guide while the robot applies pressure on the combined materials.

Fig. 7 is a perspective view of the robot guide of Fig. 6, with a roller located on the curved portion of the guide.

Fig. 8 is a schematic view of two deposition chamber in series with a polymer coated carrier moving under the outer chamber while a second polymer coated carrier with an insert on top moving under the inner deposition chamber where another deposited layer is applied.

Fig. 9 is a perspective view of an automotive fascia that combines a decorative surface carrier, a polymer deposited backing, a core material and a second continuous fiber filled back layer of polymer.

Fig. 10 is a schematic view of a forming device or a vertical acting clamping press containing upper and lower sections.

Fig. 11 is a cross-sectional view of two concave sides and carriers facing each other while in holding fixtures with external heat being applied to the edges.

Fig. 12 is a cross-sectional view of the two sections in a sealed state.

Fig. 13 is a perspective view of the sealed container, open at the end, with the carrier as the inside surface.

Fig. 14 is a cross-sectional view of a polymer deposited carrier being held in place by a vacuum system in the undercarriage, positioned within a forming device with a core

65,084-0002

forming section on the upper half and a cavity section on the bottom, side guides to move the undercarriage into the press and outboard clamps that position and hold the carrier over the cavity and core to allow the undercarriage to move out of the clamping device.

Fig. 15 is a cross-sectional view of a carrier adhering to a deposited polymer layer, a honeycomb core insert and a second layer of deposited polymer located over the insert.

Fig. 16 is a partial cross-sectional view of the transport device inserted to a polymer collection chamber, a layer of fiber being driven into the chamber and a carrier passing below the chamber.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to Fig. 1, where the polymer transfer and deposition device is designated by the letter A. It includes plasticating machine or extruder 10 shown with remotely located combinations of multiple or a plurality of clamp stations 12 and a plurality of single site clamping stations 14. A dual outlet polymer distribution manifold 16 with shut off controls 28 for each outlet 30 is attached to the plasticating machine 10 while depositing the plasticized polymer into the chamber of a transport device 18. Additional transport devices 20 are positioned in front of the clamping stations 12 and 14 for returning to the manifold 16 polymer dispensing outlet. The transport device guide or conveyor 22 handles the outer transport movement while transport device guide or conveyor 24 controls the inner transport movement.

The arrangement or layout of the clamping stations 12 and 14 are for illustrations purposes. As shown in Fig. 10, each vertical acting clamping station 14 includes mold sections 15 which are attached to vertically spaced apart platens 13 constituting a forming device. A fluid cylinder or actuator 25 is attached to the upper platen 13 for moving the platen 13 up and down on the guides 17. The size and number of stations can be adjusted to meet a specific requirement.

The four illustrated transport devices 18 and 20 of Fig. 1 are shown with the inner, bottom transport device 20 serving clamping stations 12 and 14 on the bottom left side as illustrated. The top transport device 18 handles the upper left clamping station 14 as illustrated. The two outer transport devices 20 serve the outer top and bottom clamping stations 12 respectively as illustrated in Fig. 1. One or more cylinders are attached to the transport devices 18, 20, providing the pressure to move a ram 36 located within the transport chamber 34, as shown in Fig. 3. The number of cylinders on each transport device 18, 20 depends on the size of the chamber 34. The overall dimensions of chamber 34 and the position of the ram 36 therein determine the available volume within the chamber 34. When a molten polymer is deposited in the transport chamber 34, the transport device 18, 20 is insulated and/or heated. Although not illustrated, necessary electrical, pneumatic and hydraulic components are attached to the transport device 18, 20.

Referring now to Fig. 2, the polymer distribution manifold 16 has two outlet ports 30 for providing a continuous discharge of the polymer, with alternating on-off shut off devices 28 located at the outlet ports 30. When the outside transport chamber 34 is collecting discharging polymer, the mating shut off device 28 is in the open position and the inner shut off device 28 is in the closed position. The shut off devices 28 are reversed when the inside transport chamber 34 is collecting polymer.

To allow polymer discharge from the dual outlet manifold 16 into chamber 34 of the transport device 18, 20, a fill port 38 is opened using a toggle lift and rotation clamp 37. As link 39 is retracted, the toggle clamp 37 lifts the port 38 and rotates it away from the opening 38a. In the close position, the toggle clamp 37 locks the fill port 38 in place in opening 38a. To discharge the polymer from the transport chamber 34, seal 40 is retracted using one or more cylinders 41, and the ram 36 pushes against the polymer within transport chamber 34, forcing the polymer out of the exit port 42.

Each movable non-rotatable and hollow transport 18, 20 has a top wall 43, a bottom wall 44 and a pair of ends walls 45. The entrance port or opening 38a is located in the top wall 43. The exit port or opening 42 is located in the bottom wall 44.

Referring now to Fig. 4, one transport and deposition device 20 that contains molten polymer within the chamber, deposits molten polymer 59 on a planar shaped carrier 60 under the forward movement of a ram which is located within the chamber. An opening is provided in the bottom of the transport device 20 where polymer exits from the chamber. The planar shaped carrier 60 moves under the transport and deposition device 20 as polymer 59 is deposited on the moving carrier 60. The combined deposited polymer and carrier index forward in a straight line towards a clamping device represented by the platens 13. Two conveyor side guides 64 with a plurality of clamp attachments 66 hold the carrier 60 during movement via drive roll 62. The combined deposited polymer 59 and carrier 60 index into a forming device represented by upper and lower platens 13 to which upper and lower mold sections 15 are attached. The forming device close on the combined carrier 60 and the deposited polymer 59 to produce an article of a desired shape.

In another aspect of the preferred embodiment, the carrier 60 passes under and collects deposited polymer 59 in both directions from the transport and deposition device 20. A light-weight core 57 is placed on the first layer of deposited polymer 59 prior to reversing the direction of carrier 60. Referring now to Fig. 5, the carrier 60 is moved under the transport and deposition device 20 in a direction away from the forming device 13 as polymer 59 is deposited on carrier 60 in a manner described in Fig. 4. An undercarriage 46 supports the carrier 60 and the deposited polymer 59, holding the carrier 60 in position with edge clamps 73. The undercarriage 46 is constructed from a light weight material containing a low friction, heat resistant surface. A multi-axis robot 47 places the rectangular shaped core 57 on the deposited polymer 59 by a rotating fixture 48 attached to the vertical acting robot arm 49. Core material 57 is collected from a feed station located outside the process area (not shown) by the multi-axis robot rotating fixture 48 using vacuum cups attached to the face of the fixture 48. Arms 50 and 52 control the

horizontal movements of the robot 47. The fixture 48 releases the core 57 on the deposited polymer 59 and moves away from the combined carrier 60, deposited polymer 59 and core 57. The combined materials move back under the transport device 20 and collects deposited polymer from the transport and deposition device 20 in the same manner as described in Fig. 4. The combined materials continue in a straight-line fashion into the forming device 13 to produce an article of a desired shape out of the combined carrier and polymer encapsulated core material. The undercarriage 46 retracts from the forming device 13 prior to forming a desired shape.

Prior to entering the forming device 13, a surface layer can be laminated to the exposed top layer of deposited polymer 59 at a position between the forming device comprising the platens 13 and the molds 15 and the transport and deposition device 20. As shown in Fig. 6, the multi-axis movement robot 47 with horizontally moving arms 50 and 52 and a vertically acting arm 49 has an attachment or robot guide 53 capable of rotating around arm 49 from a horizontal to a vertical position. The multi-axis robot 47 picks up a surface material 26 from a feed device such as a magazine (not shown) that is outside the process area. Attachment or robot guide 53 is positioned vertically with a curved lower edge or portion that guides the surface layer 26 as the combined carrier 60 and deposited polymer 59 moves under the robot guide 53. Undercarriage 46 provides horizontal movement for the combined materials under the curved edge or portion of robot guide 53. The vertical robot axis 29 applies downward acting force to improve the contact between the surface material 26 and the deposited polymer 59. Undercarriage 46 provides a counteracting force. A rotary fixture holds the surface material 26 with pneumatically operated side clamps that releases the surface material 26 at the start of the curved edge of attachment or guide 53. The interface friction between the surface material 26 and moving deposited polymer 59, together with the compressive force between the undercarriage 46 and attachment or robot guide 53, combine to move the surface material 26 at the same rate as the deposited polymer 59. Attachment or guide 53 is positioned between the transport and deposition device 20 and the forming device 13 (not shown). As an alternative to the curved edge or portion of attachment or robot guide 53, a roller 31

is attached to the curved lower edge of guide 53 as shown in Fig. 7. The roller 31 would rotate as the combined laminate moves forward.

Another method to provide a double layer of deposited polymer 59 on a carrier 60, two transport and deposition devices 20 are aligned in series so that carrier 60 passes under both transport and deposition devices 20 and accept deposited polymer 59. An insert 65 is placed between the first and second deposits of polymer 59. Fig. 8 shows a schematic view of two transport and deposition devices 20 with a carrier 60 passing under the outer or left device 20. Polymer 59 is deposited on carrier 60 as the carrier moves towards a second transport and deposition device 20 using outboard drives 64 attached to carrier 60 via clamps 66. An insert 65 is placed on deposited polymer 59 using a multi-axis robot 47 as shown in Fig. 5, prior to passing under the second deposition device 20 where another layer of polymer is deposited prior to indexing into the forming device. The same or different polymers 59 can be deposited from each transport and deposition device 20.

To describe an application that utilizes the combination of a carrier 60, polymer 59 and an insert 57, Fig. 9 is a cut-away view of an automotive fascia and bumper combination where carrier 60 becomes a decorative outer surface. Deposited polymer 59 adheres to the carrier 60 and provides structure. A core material 57 is encapsulated by polymer 59 and acts as a beam. A continuous fiber reinforced polymer 59a makes up the back support of the composite. The process to produce continuous fiber reinforced melt deposits is referenced in my copending U.S. Patent application, Ser. No. 09/388,052.

In reference to a forming device represented by the platens 13, the preferred embodiment is shown in Fig. 10. The front view of the forming device consists of upper and lower platens 13 and forming molds 15 attached to the vertical supports 14. The upper portion of the forming device moves up and down on guides 17 under the forces applied by an actuator 25. The carrier 60 and deposited polymer 59 are positioned between mold sections 15. The downward action of the forming device forces the mold sections 15 to

65,084-0002

close over the combined carrier 60 and deposited polymer 59 to produce an article with the desired shape.

In another embodiment, the carrier 60 side of a composite is formed over the core or convex side of a mold half 15. The preferred carrier 60 is a fluoropolymer composition that has been treated to modify the surface of one side to improve adhesion to the deposited polymer 59. Two of the finished articles or parts, with or without the same shape, would have edges that align with each other that are fused together to form a closed container 120. Fig. 11-13 shows the steps used to produce a sealed container 120. Fig. 11 is a cross-sectional view of holding fixtures 109 used to position two mating, concave shaped finished articles or parts that face each other with the carrier film 60 on the inside of the concave shape and the solidified deposited polymer 59 on the outside. The carrier sides 60 extend to matching flanges 112 where external infrared heat 105 is selectively applied to the flange areas to soften the carriers. Once the material has softened and can flow under pressure, the two mating edges of the carriers 60 are fused together under the pressure of actuators 107. The heat source 105 is separated from the holding fixture 109 prior to part fusion. Fig. 12 is a cross-section of the fused container 120 showing fused flanged edges. Fig. 13 is a cut-away view of the sealed container 120.

In reference to an undercarriage 46, Fig. 14 shows the undercarriage 46 positioned between the upper and lower half's of the mold 15 within a clamping or forming device 13. The upper mold half 15a is the core or convex side and the lower hold half 15b is the cavity or concave side. The carrier 60 has a layer of deposited polymer 59 on the top surface. The carrier 60 is held in place on the undercarriage 46 by a series of vacuum ports 71. The undercarriage 46 is supported and moves on guides 51 positioned on each side of the lower platen 13. An extender section 21 connects the undercarriage 46 with the guides 51 to allow the guides 51 to be positioned outside of the mold 15. On opposite sides of the forming device 13, pneumatic actuated grips are part of an actuator 19 that can move above the extended section 21 to grip the edges of the carrier 60 on two sides. The actuator 19 lifts the carrier 60 and deposited polymer 59 off the undercarriage 46 until the

65,084-0002

undercarriage 46 retracts from the forming press 13 after breaking the vacuum hold. The actuators 19 can lower the carrier 60 and keep the carrier 60 in tension until the closing mold halves pull the carrier 60 out of the end grips 11.

Fig. 15 shows a typical cross-section of a part that incorporates features described in this invention. A honeycomb structure 57 is encapsulated on both sides by deposited polymer 59. A surface material 55 adheres to the lower deposited polymer 59. Specific desirable properties can be incorporated in the composite by modifying any of the components.

The polymer transfer and deposition device of Fig. 16 shows the transport device 20 aligned with the top of a polymer collection device 72. As the transport device 20 moves forward to combine with the collection device 72, a hinge 78 is pushed to open a space 70 where polymer, located in chamber 34, can be deposited into the collection chamber 72 at a controlled rate. A roll or spool of fiber 76 unwinds and moves through an opening 81 located near or on top of the polymer collection device 72.

The set of drivers 80 pull the fibers 76 into the chamber 72 at a controlled rate. The drivers 80 can move the fiber 76 in a continuous or discontinuous manner. A set of rotating impellers 83 apply inward acting force to the polymer and fibers or fiber mix. Baffles 77 are laterally spaced apart from impellers 83. Once the polymer transport device 20 has delivered a set amount of polymer, it retracts, allowing hinge 78 to close, and returns the transport device to the plasticating machine 10 where more polymer can be deposited into chamber 34. The exit position 75 of the polymer coated fiber is adjustable to control the ratio of polymer to fiber. The exit position 75 opening is controlled by seal 40 attached to one or more pistons 41. Seal 40 has a blade edge that can cut the existing polymer composite to any desired length. The existing polymer composite can be deposited on carrier 60 and moved into a clamping station. Cutters 85 chop fibers to any desirable length. The collection device 72 can be moved on a track system that is similar

65,084-0002

to the method used to guide the transport devices 18, 20 to the various clamp stations 12 and 14.

This invention described above may be modified or have changes made to it within the scope of the invention as defined by the attached claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223